



- NOTES:

  1. EDGES OF STONE DUST TO BE TAMPED ON A 45' ANGLE.

  2. TIE IN TOPSOIL AND SEED TO MATCH EXISTING.





NOTE: CONCRETE TO BE 30MPa, 7.0% ± 1.5% AIR CONTENT, SLUMP 70mm ± 20mm.

# TYPICAL CONCRETE SIDEWALK

50mm HL3 150mm GRANULAR 'A'

300mm GRANULAR 'B', TYPE II

### LIGHT DUTY ASPHALT N.T.S.



150mm GRANULAR 'A' 400mm GRANULAR 'B', TYPE II, OR,

## GRAVEL DRIVE/PARKING

## OPSS SPECIFICATIONS

THE MUNICIPAL—ORIENTED ONTARIO PROVINCIAL STANDARDS IN AFFECT WHEN THE CALL FOR TENDERS FOR THIS CONTRACT WAS ADVERTISED SHALL APPLY FOR THE DURATION OF THE CONTRACT. ALL REFERENCES WITHIN THIS SPECIFICATION TO AN OPSS SHALL BE DEEMED TO MEAN OPSS.MUNI, UNLESS USE OF A PROVINCIAL—ORIENTED SPECIFICATION TO ACORRESPONDING MUNICIPAL—ORIENTED SPECIFICATION, THE REFERENCES BELOW SHALL BE CONSIDERED TO BE THE OPSS LISTED, UNLESS USE OF A PROVINCIAL—ORIENTED SPECIFICATION, THE REFERENCES DELOW SHALL BE CONSIDERED TO BE THE OPSS LISTED, UNLESS USE OF A PROVINCIAL—ORIENTED SPECIFICATION IS SPECIFIED IN THESE CONTRACT DOCUMENTS.


DOCUMENTS.
THE FOLLOWING ONTARIO PROVINCIAL STANDARD SPECIFICATIONS APPLY
TO AND FORM PART OF THIS CONTRACT:

CONTRACT:	
MUNI 120	127
MUNI 180	201
MUNI 212	310
351	MUNI 353
MUNI 401	MUNI 402
405	407
MUNI 410	MUNI 441
490	MUNI 501
MUNI 510	MUNI 517
MUNI 539	MUNI 706
803	MUNI 804
MUNI 1002	MUNI 1003
MUNI 1010	MUNI 1101
1150	1301
MUNI 1303	1305
1308	1312
MUNI 1820	1841
	MUNI 180 MUNI 212 351 MUNI 401 405 MUNI 410 490 MUNI 510 MUNI 539 803 MUNI 1002 MUNI 1010 1150 MUNI 1303


ONTARIO PROVINCIAL STANDARD SPECIFICATIONS (OPSS) AND ONTARIO PROVINCIAL STANDARD DRAWINGS (OPSD) FORM PART OF THIS CONTRACT. THE TEXT OF ALL OPSS'S IS CONTAINED IN THE MANUAL "ONTARIO PROVINCIAL

THE OPSD'S ARE CONTAINED IN THE MANUAL OF ONTARIO PROVINCIAL STANDARD DRAWINGS.

## **LEGEND**



PROPOSED BUILDING



### **GENERAL NOTES**

 ALL WORK ON CITY PROPERTY TO BE PERFORMED BY A CONTRACTOR APPROVED BY

- CONTRACTOR TO VERIFY ALL DIMENSIONS
  AND ELEVATIONS PRIOR TO THE START OF CONSTRUCTION
- CONTRACTOR TO OBTAIN ALL NECESSARY PERMITS PRIOR TO START OF CONSTRUCTION

- NOTES: EROSION & SEDIMENT CONTROL

  IN ACCORDANCE WITH BEST MANAGEMENT PRACTICES FOR EROSION & SEDIMENT CONTROL:

  GEOTEXTILE CATCHES SHALL BE INSTALLED UNDER THE LIDS OF ALL EXISTING AND PROPOSED SITE STRUCTURES AND ADJACENT MUNICIPAL STRUCTURES. "ULTRA DRAIN GUARD" OR EQUAL.

  LIGHT DUTY SILT FENCE AND STRAW BALE CHECKS SHALL BE INSTALLED AT LOCATIONS AS SHOWN ON THE DRAWING.

  ALL SEDIMENT AND EROSION CONTROL MEASURE SHALL BE INSPECTED DAILY AND AFTER EVERY PRAIN EVENT BY THE CONTRACTOR. ALL SEDIMENT AND EROSION MEASURES SHALL BE INSPECTED DAILY AND AFTER EVERY PRAIN EVENT BY THE CONTRACTOR. ASSEDIMENT AND EROSION MEASURES SHALL BE MISSPECTED TO SHALL BE MOST OF THE STALL BE MADE OF THE STALL B
- THIS DOCUMENT IS TO BE CONSIDERED A LIVING DOCUMENT AND MAY BE AMENDED IF WARRANTED BY CONDITIONS.

CONTRACTOR TO CONTACT UTILITY
COMPANIES TO DETERMINE TYPE,
LOCATION, AND CONFIGURATION OF
EXISTING PLANT.

**BENCHMARK** 

NOTE:

No.	Ву	Date	Revisions

All drawings, specifications and related documents are the copyright property of the Engineer and must be returned upon request. Reproduction of drawings specifications, and related documents in part or who is forbidden without the Engineers' written permission

The contractor must check and verify all dimensions on the job prior to start of construction.

Drawings are not to be scaled.





Apex Building Telephone: (613) 345-0400
207 - 100 Strowger Blvd. Facsimile: (613) 345-0008
Brockville, Ont. K6V 5J9 www.EastEng.com

PECK'S MARINA **BOAT STORAGE** 

**DETAILS** 

CAJ CAJ