



NOTES:

1. EDGES OF STONE DUST TO BE TAMPED ON A 45' ANGLE.

2. TIE IN TOPSOIL AND SEED TO MATCH EXISTING.





NOTE: CONCRETE TO BE 30MPa,  $7.0\% \pm 1.5\%$  AIR CONTENT, SLUMP 70mm  $\pm$  20mm.

TYPICAL CONCRETE SIDEWALK

50mm HL3 150mm GRANULAR 'A'

300mm GRANULAR 'B', TYPE II

LIGHT DUTY ASPHALT N.T.S.

150mm GRANULAR 'A' 400mm GRANULAR 'B', TYPE II, OR,

GRAVEL DRIVE/PARKING

## OPSS SPECIFICATIONS


THE MUNICIPAL—ORIENTED ONTARIO PROVINCIAL STANDARDS IN AFFECT WHEN THE CALL FOR TENDERS FOR THIS CONTRACT WAS ADVERTISED SHALL APPLY FOR THE DURATION OF THE CONTRACT. ALL REFERENCES WITHIN THIS SPECIFICATION TO AN OPSS SHALL BE DEEMED TO MEAN OPSS.MUNI, UNLESS USE OF A PROVINCIAL—ORIENTED SPECIFICATION IS SPECIFIED IN THESE CONTRACT DOCUMENTS. WHEN THERE IS NOT A CORRESPONDING MUNICIPAL—ORIENTED SPECIFICATION, THE REFERENCES BELOW SHALL BE CONSIDERED TO BE THE OPSS LISTED, UNLESS USE OF A PROVINCIAL—ORIENTED SPECIFICATION IT THESE CONTRACT DOCUMENTS.

A PROVINCIAL—OUTLIFITED SI CONTROLLA STANDARD SPECIFICATIONS APPLY
TO AND FORM PART OF THIS CONTRACT:
102 MUNI 120 127
128 MUNI 180 201 102 128 MUNI 206 MUNI 314 MUNI 355 MUNI 403 201 310 MUNI 353 MUNI 402 MUNI 212 351 MUNI 401 405 408 MUNI 442 506 MUNI 518 MUNI 410 490 MUNI 510 MUNI 441 MUNI 501 MUNI 517 MUNI 539 MUNI 706 803 MUNI 804 MUNI 1002 MUNI 1010 1150 MUNI 1003 MUNI 1101 1301 1305 1312 1841 1001 MUNI 1004 MUNI 1102 1302 MUNI 1303 1308 MUNI 1820 2501 1306 MUNI 1315 1850

ONTARIO PROVINCIAL STANDARD SPECIFICATIONS (OPSS) AND ONTARIO PROVINCIAL STANDARD DRAWINGS (OPSD) FORM PART OF THIS CONTRACT. THE TEXT OF ALL OPSS'S IS CONTAINED IN THE MANUAL "ONTARIO PROVINCIAL

THE OPSD'S ARE CONTAINED IN THE MANUAL OF ONTARIO PROVINCIAL STANDARD DRAWINGS.

## **LEGEND**





 ALL WORK ON CITY PROPERTY TO BE PERFORMED BY A CONTRACTOR APPROVED BY

TO BE REMOVED

PROPOSED BUILDING

- CONTRACTOR TO VERIFY ALL DIMENSIONS
  AND ELEVATIONS PRIOR TO THE START OF CONSTRUCTION
- · CONTRACTOR TO OBTAIN ALL NECESSARY PERMITS PRIOR TO START OF CONSTRUCTION

NOTES: EROSION & SEDIMENT CONTROL

IN ACCORDANCE WITH BEST MANAGEMENT PRACTICES FOR EROSION & SEDIMENT CONTROL:

- GEOTEXTILE CATCHES SHALL BE INSTALLED UNDER THE LIDS OF ALL EXISTING AND PROPOSED SITE STRUCTURES AND ADJACENT MINICIPAL STRUCTURES. "ULTRA DRAIN GUARD" OR EQUAL.

- LIGHT DUTY SILT FENCE AND STRAW BALE CHECKS SHALL BE INSTALLED AT LOCATIONS AS SHOWN ON THE DRAWING.

- ALL SEDIMENT AND EROSION CONTROL MEASURE SHALL BE INSTALLED AT LOCATIONS AS SHOWN ON THE DRAWING.

INSPITED TO BE ADDITIONAL SEDIMENT AND EROSION ENGINESS SHALL BE MAINTAINED, REPAIRED OR REPLACED AS REQUIRED UNTIL CONSTRUCTION IS COMPLETE AND GROUND COVER HAS STABILIZED. THE CONTRACTOR SHALL IMMEDIATELY CONTAIN AND REMOVE ANY SEDIMENTS THAT BREACH SILT BARRIERS.


- CONSTRUCTION TRUCKS SHALL NOT BE CLEANED OR WASHED OFF ON THIS SITE EXCEPT AT AN APPROVED WASH OFF STATION. ANY FUEL SPILLS SHALL BE CONTAINED & CLEANED UP IMMEDIATELY. THE MINISTY OF THE ENVIRONMENT MUST BE NOTIFIED IMMEDIATELY IF A SPILL OCCURS.

- IN THE EVENT THAT THE EROSION AND SEDIMENT CONTROL (\*ESC\*) MEASURE INDICATED ON THIS PLAN ARE NOT SUFFICIENT, THE CONTRACTOR SHALL PROVIDE ADDITIONAL "ESC\* MEASURED TO MINIMIZE THE RELEASE OF SOILS AND SEDIMENT INTO BODIES OF WASTER AND SEWERS.


- CONTRACTOR IS RESPONSIBLE FOR REMOVAL OF EROSION CONTROL MEASURES UPON COMPLETION OF CONSTRUCTION AND RE-VEGETATION HAS OCCURRED.

- CONTRACTOR IS RESPONSIBLE FOR DISPOSAL OF COLLECTED SEDIMENT.

CONTRACTOR IS RESPONSIBLE FOR DISPOSAL OF COLLECTED SEDIMENT.
 THIS DOCUMENT IS TO BE CONSIDERED A LIVING DOCUMENT AND MAY BE AMENDED IF WARRANTED BY CONDITIONS.



**BENCHMARK** NOTE: CONTRACTOR TO CONTACT UTILITY
COMPANIES TO DETERMINE TYPE,
LOCATION, AND CONFIGURATION OF
EXISTING PLANT.




All drawings, specifications and related documents are the copyright property of the Engineer and must be returned upon request. Reproduction of drawings, specifications, and related documents in part or whole is forbidden without the Engineers' written permission.

The contractor must check and verify all dimensions on the job prior to start of construction.

Drawings are not to be scaled.





CAJ

Horizontal: 400